

Corner originally set as a post in 1820 by Wm. B. Laughlin with the following witnesses: 14" beech bearing south 19 degrees, thence west 14 links; and a 16" dogwood bearing north 19 degrees, thence east 24 links. (M.C. Atlas p. 24) A survey by J.A. Hasbrook on October 2,1876 indicates no stone or witnesses. (Perry Legal Book p. 45) Corner referenced by Monroe on 4/20/53 and called a stone. Corner referenced by Scherschel on 10/23/70 and called a iron pin. Corner referenced by Wilcoxen on 6/19/75 and called a brass plug. Corner referenced by Miller on 6/26/86 and called a brass plug. Corner referenced by Whiteside on 5/20/96 and called a brass plug in steel box. Corner referenced by Whiteside on 8/19/01 and called a brass plug. Corner excavated by Wilcoxen on 10/6/04 and a brass plug in steel box was found. No other points were found. A#205 cast iron Harrison monument was set in position as the corner.

	14032302	
REF.	DISTANCE	DESCRIPTION
1,	54.14	PK nail SW PwP#330-785 4"up
2,	123.48'	Mag nail w/brass washer W PwP no# 12"up
3.	96.77	PK nail E guy pole #212-784 12"up
4,	68.74	PK nail NE PwP#507-84 12"up
5.	131.90'	SE corner of brick/frame home ADDRESS 506